

CP-0802X

8+2 Port Industrial Managed PoE+ L3 Switch with 10G Uplink



- 8x Gigabit Ethernet ports with IEEE 802.3at PoE+
- 2x 1/10 Gigabit Ethernet SFP+ Slot
- Built for harsh environments and wide temperature range application
- RSTP, MSTP, ERPS, LACP for Network Redundancy
- QoS CoS/DSCP to increase determinism
- Supports IGMP Snooping v1/v2/v3, up to 512 groups
- DHCP Relay Option 82 for policies IP address assignment
- SNMP v1/v2c/v3 for network management
- Supports Storm Protection
- USB storage for configuration-free replacement
- Supports industrial automation protocols Ethernet/IP and Modbus TCP
- Supports PoE PD Alive Check Function for PoE Device Power Recycle



Specifications

Technology

- IEEE 802.3 10BaseT
- IEEE 802.3u 100BaseTX
- IEEE 802.3ab 1000BaseT
- IEEE 802.3ae 10GBase over Fiber
- IEEE 802.3x Flow Control
- IEEE 802.3af Power over Ethernet
- IEEE 802.3at PoE+
- IEEE 802.3ad/802.1AX LACP
- IEEE 802.1D Spanning Tree Protocol
- IEEE 802.1w Rapid STP
- IEEE 802.1s Multiple STP
- ITU-T G.8032 / Y.1344 ERPS
- IEEE 802.1Q VLAN Tagging
- IEEE 802.1ad Stacked VLANs
- IEEE 802.1p Class of Service
- IEEE 802.1X Network Authentication
- IEEE 802.1AB LLDP
- IEEE 1588 PTP

Standards

Processing Type Store and Forward

Switch Properties

Switch Fabric 56Gbps
Priority Queues 8 Queues
Jumbo Frame 9216bytes
MAC Table Size 16K
Packet Buffer 12Mbits
VLAN Table Size 4094

IGMP Group 512

ACL Group 512

VLAN IP Entries 64

Routing Entries (IPv4/IPv6) 512/256 host, 64/64 LPM

Software Feature

Network Redundancy RSTP, MSTP, G.8032 ERPSv2, Port Trunking with LACP

Security 802.1X, RADIUS, TACACS+, SSL, SSH

Management IPv4, IPv6, Web, Telnet, Serial Console, CLI, SNMP v1/v2c/v3, uPnP

Diagnostics RMON, SNMP Inform/Trap, Syslog, SMTP, Port Mirroring, LLDP, DDM

Configuration DHCP Server/Client, Relay Option 82, TFTP, USB

Filter 802.1Q VLAN, Q-in-Q, IGMP Snooping v1/v2/v3, IGMP Querier, Independent Vlan Learning

Time Sync. NTP, IEEE1588v2 OC (Software Timestamp), BC (Software Timestamp), TC (Hardware Timestamp)

QoS CoS, DSCP, WRR/SPQ Queuing, Storm Protection

PoE Powering Status, PoE Monitoring, Scheduling, PD Alive Check, PoE Priority

Industrial Profiles	Ethernet/IP, Modbus TCP
L3 Switching	Static Routing, RIP v1/v2, OSPF v2, VRRP v2
Interface	
RJ45 Port	8x 10/100/1000T(x) with PoE+, auto negotiation speed duplex mode, auto MDI/MDI-X
Fiber Port	2x 1/10 Gigabit Ethernet SFP+ Slot
PoE Pin Out	V+, V+, V-, V-, for pin 1, 2, 3, 6, Endspan, MDI Mode A
LED Indicators	Per unit: PWR1, PWR2, Fault, Ring Master, Ring State Ports: Link/Active with highest speed(Green), low speed(Amber) PoE: Output Power
Alarm Contact	1x relay output with current carrying capacity of 1A @ 24 VDC
Digital Inputs	1x isolated input from the electronics. +13 to +30V for state "1" -30 to +3V for state "0" Max. input current: 8mA
Button	Multiple functions reset button
Serial Console	1x RS232 in RJ45 connector with console cable, 115.2Kbps, 8N1
Storage	1x USB 2.0 storage for firmware update, configuration backup, restore, boot up and syslog
Power Requirements	
Operation Voltage	48-57VDC, redundant dual inputs, >50VDC for PoE+ output recommended
Connection	1x removable 4-contact terminal block
Power Consumption	0.35A@48VDC without PDs' consumption
PoE Power Budget	Max. 240 W for total PD consumption, Max. 30 W per PoE port
Protection	Overload Current Protected, Reverse

Features with star(*) implies those are under development.

In a continuing effort of improvement and updated technology, product specifications are subject to change without notice.

Polarity Protected

Mechanical Construction

Enclosure	Aluminum
Protection Class	IP30
Dimensions	72x145x118 mm (WxHxD)
Weight	0.90 kg
Mounting	DIN-Rail Mounting, Optional Wall Mounting Kits


Environmental Limits

Operating Temperature	Standard: -10°C ~ 60°C (14°F ~ 140°F) Extended: -40°C ~ 75°C (-40°F ~ 167°F) For 10G SFP+: -40 ~ 60°C (32°F ~ 140°F)
Storage Temperature	-40°C ~ 85°C (-40°F ~ 185°F)
Ambient Relative Humidity	5 to 95%, (Non-Condensing)

Regulatory Approvals

EMI	CE EN 55032 Class A
EMS	IEC61000-4-2 (ESD) IEC61000-4-3 (RS) IEC61000-4-4 (EFT) IEC61000-4-5 (Surge) IEC61000-4-6 (CS) IEC61000-4-8 (Magnetic Field)
Free Fall	IEC60068-2-32
Shock	IEC60068-2-27
Vibration	IEC60068-2-6
Green	RoHS Compliant
Certifications	UL 60950-1/62368 (Pending) EN 50121-4
MTBF	>100,000 hours
Warranty	5 Years

Dimensions (unit = mm)



Ordering Information

CP-0802X	8+2 Port Industrial Managed PoE+ L3 Switch with 10G Uplink - 8x 10/100/1000T(x) with 30W PSE + 2x 1/10 Gigabit Ethernet SFP+ Slot - Operating Temperature: -10°C ~ 60°C (14°F ~ 140°F)
CP-0802X-T	8+2 Port Industrial Managed PoE+ L3 Switch with 10G Uplink - 8x 10/100/1000T(x) with 30W PSE + 2x 1/10 Gigabit Ethernet SFP+ Slot - Operating Temperature: -40°C ~ 75°C (-40°F ~ 167°F) For 10G SFP+: -40 ~ 60°C (-40°F ~ 140°F)

Optional Accessories

NDR-240-48	Industrial DIN-Rail Power Supply with 48VDC Output, provide max. 240W Power
NDR-480-48	Industrial DIN-Rail Power Supply with 48VDC Output, provide max. 480W Power